Settingliste Federbein

Artikelnummer:	**18157P69**	**Typ:**	**5018**
Modellbezeichnung: (ohne Jahresangabe)	**FE 450 / 501 Husqvarna**	**Druckstufen-ventil:**	**DCC 10 cpl. XC '07** 5018.0213S10

	Fahrer Komfort	STANDARD	Fahrer Sport	volle Nutzlast
Druckstufendämpfung Low Speed (Klicks offen bzw. Markierung)	20	18	16	
Druckstufendämpfung High Speed (Umdrehungen offen)	2.5	2	1.5	
Zugstufendämpfung (Klicks offen bzw. Markierung)	20	18	16	
Federvorspannung	15 mm	15 mm	15 mm	mm
Preload Adjuster (Umdrehungen vorsp.)				

Statischer Durchhang	30 mm
Fahrtdurchhang	100 mm
Gasdruck	10 bar
Öl Type	50180751
Öl Viskosität	SAE 2.5

Nadel	
Höhe Scheibe Zugstufe	8 mm
Hub	139 mm
Einbaulänge	490 mm
Gummipuffer	50181077

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge	Teilenummer
Feder weicher	65/75 kg	54 N/mm	(65/62) 54-260	260 mm	91210103
Feder STANDARD	75-85 kg	57 N/mm	(65/62) 57-260	260 mm	91210104
Feder härter	85/95 kg	60 N/mm	(65/62) 60-260	260 mm	91210105

Shims Kolben 1

Stk	Druckstufe	Stk	Zugstufe
1	Ø 16x20x0.20	1	Ø 16x21x0.30
1	Ø 16x23x0.25	1	Ø 16x28x0.25
1	Ø 16x24x0.25	1	Ø 16x30x0.25
1	Ø 16x26x0.20	1	Ø 16x32x0.25
1	Ø 16x28x0.20	1	Ø 16x34x0.25
1	Ø 16x30x0.20	1	Ø 16x36x0.25
1	Ø 16x32x0.20	1	Ø 16x38x0.25
1	Ø 16x34x0.20	1	Ø 16x28x0.15
1	Ø 16x36x0.20	2	Ø 16x40x0.20
1	Ø 16x38x0.20		
1	Ø 16x40x0.20		
2	Ø 16x42x0.20		
3	Ø 16x44x0.20		
1	Ø 16x28x0.10		
4	Ø 16x44x0.20		

Kolben Nummer	50180786E
Kolben Freibohrung	0,00 mm

Shims Kolben 2

Stk	Druckstufe	Stk	Zugstufe
	Ø		Ø

Kolben Nummer	
Kolben Freibohrung	0,00 mm

Details Druckstufenventil:

Stk.	Bezeichnung, Dimension
1	Einstellfeder DCC C16
1	Backpl. Ø6x9,5x0,30
1	Shim Ø6x14x0,25
1	Shim Ø6x16x0,25
1	Shim Ø6x18x0,25
2	Shim Ø6x20x0,25
1	Shim Ø6x22x0,15
1	Shim Ø6x14x0,10
1	Shim Ø6x22x0,25

Legende:	TBD = to be defined (noch zu definieren)	- = keine Angabe

Bemerkungen:

Index	Datum	Name	Änderungsbeschreibung
a	22.04.2015	B.Meyer	Serienfreigabe

Name Ersteller:	S. Simpson
Datum Erstellung:	17.09.2014

Freigabefeld

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Shock setting list

PERFORMANCE SYSTEMS

Article number:	**18157P69**	**Type:**	**5018**
Modeldescription: (without modelyeardeclaration)	**FE 450 / 501 Husqvarna**	**Compression damping valve:**	**DCC 10 cpl. XC '07** 5018.0213S10

	Driving comfort	STANDARD	*Driving sport*	*max. payload*
Compression damping Low Speed (clicks open or marking)	*20*	18	*16*	
Compression damping High Speed (turns open)	*2.5*	2	*1.5*	
Rebound damping (clicks open or marking)	*20*	18	*16*	
Spring preload	*15 mm*	15 mm	*15 mm*	*mm*
Preload Adjuster (turns preload)				

Static sag	30 mm
Riding sag	100 mm
Gas pressure	10 bar
Oil type	50180751
Oil viscosity	SAE 2.5

Needle	
Rebound disk height	8 mm
Stroke	139 mm
Shock length	490 mm
Bump rubber	50181077

Spring	Riders weight	Spring rate	Spring description	Spring length	Part number
Spring softer	*65/75 kg*	*54 N/mm*	*(65/62) 54-260*	*260 mm*	*91210103*
Spring STANDARD	75-85 kg	57 N/mm	(65/62) 57-260	260 mm	91210104
Spring harder	*85/95 kg*	*60 N/mm*	*(65/62) 60-260*	*260 mm*	*91210105*

Shims piston 1

Qty	Compression	Qty	Rebound
1	Ø 16x20x0.20	1	Ø 16x21x0.30
1	Ø 16x23x0.25	1	Ø 16x28x0.25
1	Ø 16x24x0.25	1	Ø 16x30x0.25
1	Ø 16x26x0.20	1	Ø 16x32x0.25
1	Ø 16x28x0.20	1	Ø 16x34x0.25
1	Ø 16x30x0.20	1	Ø 16x36x0.25
1	Ø 16x32x0.20	1	Ø 16x38x0.25
1	Ø 16x34x0.20	1	Ø 16x28x0.15
1	Ø 16x36x0.20	2	Ø 16x40x0.20
1	Ø 16x38x0.20		
1	Ø 16x40x0.20		
2	Ø 16x42x0.20		
3	Ø 16x44x0.20		
1	Ø 16x28x0.10		
4	Ø 16x44x0.20		

Piston number	50180786E
Piston bleed	0 mm

Shims piston 2

Qty	Compression	Qty	Rebound
	Ø		Ø

Piston number	
Piston bleed	0 mm

Details compression unit:

Qty	Description, dimension
1	Adjusting spring DCC C16
1	Backpl. Ø6x9,5x0,30
1	Shim Ø6x14x0,25
1	Shim Ø6x16x0,25
1	Shim Ø6x18x0,25
2	Shim Ø6x20x0,25
1	Shim Ø6x22x0,15
1	Shim Ø6x14x0,10
1	Shim Ø6x22x0,25

Legend:	TBD = to be defined	- = no comment

Note:

Index	Date	Name	Modification description
a	2015-04-22	B.Meyer	production release

Draftsman:	S. Simpson
Creation date:	2014-09-17

Release stamp

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.