

KAWASAKI

KAF 400RR Mule SX (MY25)

ENGINE	
Туре	Air-cooled single-cylinder 4-stroke OHV
Capacity	401cc
Max Power (kW)	9.9kW @ 4,000rpm
Max Torque (Nm)	29.0Nm @ 2,400rpm
Transmission	2-speed automatic plus reverse
Clutch Type	Centrifugal clutch
Final Drive	CVT belt drive torque converter
Starting System	Electric CDI
CHASSIS	
Frame	Ladder type, tubular steel
Front Tyre	24 x 9.00-10
Rear Tyre	24 × 11.00-10
Front Suspension	MacPherson strut - 78mm
Rear Suspension	Unit swingarm - 79mm
Front Brakes	Dual hydraulic drums
Rear Brakes	Dual hydraulic drums (mechanical parking brake)
MEASUREMENTS	
Dimensions (L x W x H)	2,710 x 1,335 x 1,800mm
Seat Height	780mm
Wheelbase	1,780mm
Ground Clearance	170mm (unladen)
Kerb Weight	468kg
Tank Capacity	16L

DISCLAIMER: Biker's Warehouse endeavours to ensure that all data provided is done so accurately but cannot provide any warranty or guarantee as to the accuracy, timeliness, performance, completeness or suitability of this data. Public use of this data is done so with the knowledge and acceptance that Biker's Warehouse is wholly exempt from any direct, incidental or consequential loss or damage that may arise from the use of or reliance of any such data. Biker's Warehouse reserves the right to change any data herein without prior notice.

