



HONDA

CRF1100D Africa Twin DCT (MY24)

ENGINE

Type	Liquid-cooled, 4-stroke, OHC 8-valve parallel twin
Capacity	1,084cc
Max Power (kW)	75kW @ 7,500rpm
Max Torque (Nm)	112Nm @ 5,500rpm
Transmission	6-speed
Clutch Type	Dual clutch transmission (DCT) with coil springs
Final Drive	O-ring sealed chain
Starting System	Electric CDI with immobiliser

CHASSIS

Frame	Semi double cradle
Front Tyre	90/90-21 M/C
Rear Tyre	150/70-R18 M/C
Front Suspension	45mm Showa cartridge-type inverted telescopic forks (optional Showa EERA electronic control unit)
Rear Suspension	Monoshock aluminium swingarm, Pro Link with Showa gas-charged damper, hydraulic preload adjuster
Front Brakes	Dual 310mm floating wave hydraulic discs, aluminium hub, 4-piston calipers, sintered metal pads (ABS)
Rear Brakes	Single 256mm wave hydraulic disc, single-piston caliper, sintered metal pads

MEASUREMENTS

Dimensions (L x W x H)	2,330 x 960 x 1,485mm
Seat Height	850/870mm (optional 825mm low seat / 885mm comfort seat)
Wheelbase	1,575mm
Ground Clearance	250mm (unladen)
Kerb Weight	242kg (244kg with electronic suspension)
Tank Capacity	18.8L

DISCLAIMER: Biker's Warehouse endeavours to ensure that all data provided is done so accurately but cannot provide any warranty or guarantee as to the accuracy, timeliness, performance, completeness or suitability of this data. Public use of this data is done so with the knowledge and acceptance that Biker's Warehouse is wholly exempt from any direct, indirect, incidental or consequential loss or damage that may arise from the use of or reliance of any such data. Biker's Warehouse reserves the right to change any data herein without prior notice.