



SUZUKI

V-STROM 250SX

ENGINE

| | |
|-----------------|---|
| Type | Liquid-cooled 4-stroke single cylinder 4-valve SOHC |
| Capacity | 249cc |
| Max Power (kW) | 19.5kW @ 9,300rpm |
| Max Torque (Nm) | 22.2Nm @ 7,300rpm |
| Transmission | 6-speed constant mesh |
| Clutch Type | Wet multi-plate |
| Final Drive | Chain |
| Starting System | Electric CDI |

CHASSIS

| | |
|------------------|--|
| Frame | Steel trellis |
| Front Tyre | 100/90-19 |
| Rear Tyre | 140/70-17 |
| Front Suspension | Telescopic oil damped coil spring |
| Rear Suspension | Swingarm with oil damped coil spring, adjustable preload |
| Front Brakes | 310mm single disc, dual-piston caliper |
| Rear Brakes | 240mm single disc |

MEASUREMENTS

| | |
|------------------------|-----------------------|
| Dimensions (L x W x H) | 2,180 x 880 x 1,355mm |
| Seat Height | 835mm |
| Wheelbase | 1,440mm |
| Ground Clearance | 205mm (unladen) |
| Kerb Weight | 167kg |
| Tank Capacity | 12L |

DISCLAIMER: Biker's Warehouse endeavours to ensure that all data provided is done so accurately but cannot provide any warranty or guarantee as to the accuracy, timeliness, performance, completeness or suitability of this data. Public use of this data is done so with the knowledge and acceptance that Biker's Warehouse is wholly exempt from any direct, indirect, incidental or consequential loss or damage that may arise from the use of or reliance of any such data. Biker's Warehouse reserves the right to change any data herein without prior notice.